



MULTIGASPRESS EN ISO 3821 NRA/L 20

According to EN ISO 3821

Suitable for all fuel gases included in the EN ISO 3821 Norm (except fluxed fuel gases) like: acetylene, LPG, MPS, natural gas, methane.

Hose Construction

Tube: Black, smooth NBR rubber compound suitable for all fuel gases included in the EN ISO 3821 Norm except fluxed fuel gases

Reinforcement: Synthetic textile yarns

Cover: Red/orange, PVC/NBR, smooth rubber compound. Resistant to ageing, weathering, pin-pricked cover to prevent blisters during use



- Pin-pricked cover
- Low permeation
- Dual colored cover following specs indication
- Flexible hose for easy handling
- Burst Pressure Value 3:1






Tolerances

According to EN ISO 3821

Refer to Technical Handbook on page TH34

Temperature Range

-25 °C (-13 °F) to +70 °C (+158 °F)

Part Number	 I.D. (mm)	 O.D. (mm)	 Working Pressure			 Weight	 min. Bend Radius	in Stock
			MPa	psi	bar			
IH30412960/40	6.3	13.3	2.0	300.0	20	0.17	50	N
IH30412962/40	9	16	2.0	300.0	20	0.21	70	N
IH30412964/40	12.5	22.5	2.0	300.0	20	0.41	105	N
IH30412965/40	16	26	2.0	300.0	20	0.44	150	N