

CABLE SN 10

Hose Construction

- Tube:** Blue, smooth, certified EPDM dielectric rubber compound ($R \geq 4 \times 10^{10} \Omega/m$)
- Reinforcement:** Synthetic textile fabrics and embedded polyamide helix
- Cover:** Blue, smooth, certified EPDM dielectric rubber compound ($R \geq 4 \times 10^{10} \Omega/m$), ageing and weather resistant



Applications







Hose specially designed for cooling and protection of electrical cables.
Resistant to hot water and detergents, where a conformity to foodstuff regulation is not required.

Tolerances

- RMA steel mandrel
- On inside diameter:**
 - ≤ I.D. 38 mm: ± 0,79 mm
 - > I.D. 38 mm: ± 1,59 mm
- Length tolerance:** ± 1 %

Temperature Range

-40 °C (-40 °F) to +90 °C (+194 °F)

IHXXXXXXXX/XX Part Number/ Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Burst Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psi	bar	MPa	psi	bar		
IH36832071/40	25	36	1,0	150,0	10	3,0	450,0	30	0,85	300
IH36832072/40	32	43	1,0	150,0	10	3,0	450,0	30	1,02	350

Zapraszamy do dystrybutora PARKER ITR:

HOSEMANN POLSKA

www.hosemann.pl

biuro@hosemann.pl

