



# CABLEPRESS B/L 10 - 20

## Hose Construction

- Tube:** Blue, smooth, certified EPDM dielectric rubber compound ( $R \geq 4 \times 10^{10} \Omega/m$ )
- Reinforcement:** Synthetic textile fabrics
- Cover:** Blue, smooth, certified EPDM dielectric rubber compound ( $R \geq 4 \times 10^{10} \Omega/m$ ), ageing and weather resistant



## Applications

Hose specially designed for cooling and protection of electrical cables.

Resistant to steam up to 2 bar/120 °C (+248 °F), hot water and detergents, where a conformity to foodstuff regulation is not required.

## Temperature Range

-40 °C (-40 °F) to +90 °C (+194 °F), with peaks up to +120 °C (+248 °F)

## Tolerances

UNI EN ISO 1307/97

### On inside diameter:

≤ I.D. 19 mm: ± 0,80 mm

> I.D. 19 mm: ± 1,20 mm

**Length tolerance:** ± 1 %

IHXXXXXXXXXX Part Number/ Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Burst Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psi	bar	MPa	psi	bar		
<b>CABLEPRESS B/L 10</b>										
IH30116165/40	10	16	1,0	150,0	10	3,0	450,0	30	0,15	80
IH30116167/40	13	19	1,0	150,0	10	3,0	450,0	30	0,20	105
IH30116168/40	16	23	1,0	150,0	10	3,0	450,0	30	0,30	130
IH30116169/40	19	26	1,0	150,0	10	3,0	450,0	30	0,35	150
IH30116164/40	25	33	1,0	150,0	10	3,0	450,0	30	0,51	190
<b>CABLEPRESS B/L 20</b>										
IH30116180/40	6	13	2,0	300,0	20	6,0	900,0	60	0,15	50
IH30116181/40	9	16	2,0	300,0	20	6,0	900,0	60	0,20	70
IH30116182/40	13	20	2,0	300,0	20	6,0	900,0	60	0,26	80
IH30116183/40	19	27	2,0	300,0	20	6,0	900,0	60	0,41	120

Zapraszamy do dystrybutora PARKER ITR:

HOSEMANN POLSKA

[www.hosemann.pl](http://www.hosemann.pl)

biuro@hosemann.pl

RUBBER MULTIUSE HOSE CABLEPRESS W.P. bar MADE IN ITALY Parker ITR