RADIOR 10

Flexible rubber hose for delivery of hot water in heating and cooling of automotive LPG and methane systems.

Hose Construction

Tube: Black, smooth EPDM nitrosamine free rubber compound

Reinforcement: Synthetic textile yarns

Cover: Smooth, black, heat, ageing and weather-resistant EPDM nitrosamine free rubber compound

Temperature Range

-30 °C (-22 °F) to + 100 °C (+212 °F)
with peaks +120 °C (+248 °F)

- Specific for cooling system
- Also used in combination with Autogas ECE 67/110 in CNG/LPG engines
- Robust structure to avoid kinking
- Burst Pressure Value 3:1

Tolerances

According to UNI EN ISO 1307
Refer to Technical Handbook on page TH34

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure MPa	Working Pressure psi	Working Pressure bar	Weight kg/m	min. Bend Radius mm	in Stock
IH30114029/100	7	13	1.0	150.0	10	0.13	50	N
IH30114030/50	15	23	1.0	150.0	10	0.35	90	Y
IH30114030/100	15	23	1.0	150.0	10	0.35	90	Y

RUBBER HOSE RADIOR 10 bar I.D. mm MADE IN ITALY Parker

Zapraszamy do dystrybutora PARKER ITR: firmy HOSEMANN POLSKA
www.hosemann.pl biuro@hosemann.pl +48 32 770 00 00