



GAMBRINUS SM WB 10

Hose Construction

- Tube:** Beige colour, non-toxic, smooth synthetic rubber compound (conforming to Italian Legislation D.M. 21-3-1973 and to the relevant CEE directive and FDA)
- Reinforcement:** Synthetic textile fabrics, embedded steel wire helix
- Cover:** Blue (WB), abrasion and weather-resistant EPDM rubber compound



Applications

Manufactured with taste and odour-free rubber, it is recommended for suction and delivery of all foodstuff containing animal or vegetable fats and oils as well as beverages such as milk, mineral water, beer, and fruit juices, wine and liqueurs (corresponding to the simulators A, B, C and D of D.M. 220 dated 26-4-93).

Temperature Range

-15 °C (+5 °F) to +70 °C (+158 °F)

Suction

Max. 0,8 bar (600 mm Hg)

Tolerances

RMA steel mandrel

On inside diameter:

≤ I.D. 38 mm: ± 0,79 mm

> I.D. 38 mm: ± 1,59 mm

Length tolerance: ± 1 %

Cleaning

Hose can be washed and sterilised with usual detergents or steam cleaned to a maximum temperature of +120 °C (+248 °F) for short periods.

Recommendations

The hose should be cleaned and left empty after use.

IHXXXXXXXXXX Part Number/ Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Burst Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psi	bar	MPa	psi	bar		
IH36242083/40	19	31	1,0	150,0	10	3,0	450,0	30	0,74	115
IH36242084/40	25	36	1,0	150,0	10	3,0	450,0	30	0,92	150
IH36242080/40	30	42	1,0	150,0	10	3,0	450,0	30	1,10	180
IH36242085/40	32	44	1,0	150,0	10	3,0	450,0	30	1,16	190
IH36242060/40	35	47	1,0	150,0	10	3,0	450,0	30	1,25	210
IH36242086/40	38	50	1,0	150,0	10	3,0	450,0	30	1,35	230
IH36242081/40	40	52	1,0	150,0	10	3,0	450,0	30	1,41	240
IH36242026/40	45	56	1,0	150,0	10	3,0	450,0	30	1,49	270
IH36242087/40	50	63	1,0	150,0	10	3,0	450,0	30	1,88	300
IH36242058/40	60	73	1,0	150,0	10	3,0	450,0	30	2,23	360
IH36242090/40	63,5	77	1,0	150,0	10	3,0	450,0	30	2,34	380
IH36242088/20	65	78	1,0	150,0	10	3,0	450,0	30	2,50	390
IH36242028/20	70	84	1,0	150,0	10	3,0	450,0	30	2,95	420
IH36242089/20	75	89	1,0	150,0	10	3,0	450,0	30	3,10	450
IH36242078/20	80	93	1,0	150,0	10	3,0	450,0	30	3,17	480
IH36242013/20	100	116	1,0	150,0	10	3,0	450,0	30	4,61	600

Zapraszamy do dystrybutora PARKER ITR:

HOSEMANN POLSKA

www.hosemann.pl

biuro@hosemann.pl

RUBBER HOSE GAMBRINUS 10 bar PER ALIM. – DM 21.03.73 E SUCC. MADE IN ITALY – Parker ITR