

# GAMBRINUS WB 10

## Hose Construction

- Tube:** Beige colour, non-toxic, smooth synthetic rubber compound (conforming to Italian Legislation D.M. 21-3-1973 and to the relevant CEE directive and FDA)
- Reinforcement:** Synthetic textile fabrics
- Cover:** Blue (WB), abrasion and weather-resistant EPDM rubber compound



## Suction

light suction 0,3 bar (230 mm Hg)

## Tolerances

- RMA steel mandrel
- On inside diameter:**
  - ≤ I.D. 38 mm: ± 0,79 mm
  - > I.D. 38 mm: ± 1,59 mm
- On outside diameter:** ± 1,59 mm
- Length tolerance:** ± 1 %

## Applications







Manufactured with taste and odour-free rubber, it is recommended for light suction and delivery of all foodstuff containing animal or vegetable fats and oils as well as beverages such as milk, mineral water, beer, and fruit juices, wine and liqueurs (corresponding to the simulators A, B, C and D of D.M. 220 dated 26-4-93).

## Temperature Range

-15 °C (+5 °F) to +70 °C (+158 °F)

## Cleaning

Hose can be washed and sterilised with usual detergents or steam cleaned to a maximum temperature of +120 °C (+248 °F) for short periods.

IHXXXXXXXXXX Part Number/ Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Burst Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psi	bar	MPa	psi	bar		
<b>GAMBRINUS WB 10</b>										
IH36242070/40	19	31	1,0	150,0	10	3,0	450,0	30	0,70	190
IH36242071/40	25	39	1,0	150,0	10	3,0	450,0	30	1,03	250
IH36242069/40	30	44	1,0	150,0	10	3,0	450,0	30	1,18	300
IH36242072/40	32	46	1,0	150,0	10	3,0	450,0	30	1,25	320
IH36242074/40	38	54	1,0	150,0	10	3,0	450,0	30	1,67	380
IH36242077/40	40	60	1,0	150,0	10	3,0	450,0	30	2,25	400
IH36242073/40	50	70	1,0	150,0	10	3,0	450,0	30	2,69	500
IH36242152/40	60	80	1,0	150,0	10	3,0	450,0	30	3,10	600
IH36242075/20	65	85	1,0	150,0	10	3,0	450,0	30	3,34	650
IH36242076/20	75	99	1,0	150,0	10	3,0	450,0	30	4,69	750
IH36242155/20	100	125	1,0	150,0	10	3,0	450,0	30	6,34	1000
<b>GAMBRINUS L WB 10</b>										
IH36242150/40	20	29	1,0	150,0	10	3,0	450,0	30	0,57	200

Zapraszamy do dystrybutora PARKER ITR:

HOSEMANN POLSKA

[www.hosemann.pl](http://www.hosemann.pl)

[biuro@hosemann.pl](mailto:biuro@hosemann.pl)